



# PORT-A-COOL DIVISION



# PORT-A-COOL



## 48" SINGLE SPEED

- Lowers temperatures by 10 - 15 degrees C
- Energy efficient 12.0 amps for pump and motor
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 370 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PAC2K481S	48" Single Speed

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
1	33900	12.0	370	2180 x 1880 x 920	156	150



## 36" HIGH PERFORMANCE

- Lowers temperatures by 10 - 15 degrees C
- Power KÜÜL, variable-speed motor with 3-year warranty
- Quieter operation
- Energy efficient 11.0 amps for pump and motor
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 240 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PAC2K36HPVS	36" High Performance

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
Variable	17000	11.0	240	1700 x 1570 x 810	91	120



## 24" HIGH PERFORMANCE

- Lowers temperatures by 10 - 15 degrees C
- Quieter operation
- Energy efficient 8.8 amps for pump and motor
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 160 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PAC2K24HPVS	25" High Performance

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
Variable	11300	8.8	160	1350 x 1270 x 640	70	50



## 16" VERTICAL TANK

- Lowers temperatures by 10 - 15 degrees C
- New cord-wrap storage
- 160 litre water reservoir for longer operation
- Energy efficient 5.1 amps for pump and motor
- Water level sight tube and sump drain
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 80 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PAC163SVT	16" Vertical Tank

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
3	6600	5.1	80	1500 x 950 x 580	59	160



# PORT-A-COOL



## JETSTREAM 2400

- Lowers temperatures by 10 - 15 degrees C
- 180 litre water reservoir for longer operation
- Power KÜÜL, variable-speed motor with 3-year warranty
- Energy efficient 9.2 amps for pump and motor
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 180 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PACJS2400	Jetstream 2400

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
Variable	12700	9.2	180	1820 x 1370 x 710	91	180



## JETSTREAM 1600

- Lowers temperatures by 10 - 15 degrees C
- 160 litre water reservoir for longer operation
- Power KÜÜL, variable-speed motor with 3-year warranty
- Energy efficient 5.3 amps for pump and motor
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 90 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PACJS1600	Jetstream 1600

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
Variable	6700	5.3	90	1500 x 940 x 620	49	160



## CYCLONE 3000

- Lowers temperatures by 10 - 15 degrees C
- Energy efficient 5.6 amps for pump and motor
- Water level sight tube and sump drain
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 60 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PAC2KCYC01	Cyclone 3000

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
2	5000	5.6	60	970 x 750 x 640	45	60



## CYCLONE 2000

- Lowers temperatures by 10 - 15 degrees C
- Energy efficient 2.5 amps for pump and motor
- Water level sight tube and sump drain
- Durable one-piece, rust-free, leak-proof molded polyethylene housing
- Environmentally friendly efficient and effective resource use
- Cools for a fraction of the cost of air conditioning
- Cools without chemicals or refrigerants
- Long-term dependability - near maintenance-free operation
- Ready to operate out of the box
- Cooling capacity is 40 sq. m.

<b>Product Code:</b>	<b>Description:</b>
*PACCY02	Cyclone 2000

SPEEDS	M <sup>3</sup> / HR	AMPS	AREA M <sup>2</sup>	DIMENSIONS h x w x d (mm)	WEIGHT kg	RESEVOIR litres
2	3300	2.5	40	790 x 610 x 640	27	40